




## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification <sup>6</sup> : <b>A61F 13/15, 13/56</b>		<b>A1</b>	(11) International Publication Number: <b>WO 99/37261</b>
			(43) International Publication Date: 29 July 1999 (29.07.99)
(21) International Application Number: PCT/IB99/00052 (22) International Filing Date: 18 January 1999 (18.01.99) (30) Priority Data: 98101175.2      23 January 1998 (23.01.98)      EP (71) Applicant (for all designated States except US): THE PROCTER & GAMBLE COMPANY [US/US]; One Procter & Gamble Plaza, Cincinnati, OH 45202 (US). (72) Inventor; and (75) Inventor/Applicant (for US only): HEINERMANN, Gregor, Heribert [DE/DE]; Im Stein 7, D-65239 Hochheim-Massenheim (DE). (74) Agents: REED, T., David et al.; The Procter & Gamble Company, 5299 Spring Grove Avenue, Cincinnati, OH 45217-1087 (US).		(81) Designated States: AL, AM, AT, AT (Utility model), AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, CZ (Utility model), DE, DE (Utility model), DK, DK (Utility model), EE, EE (Utility model), ES, FI, FI (Utility model), GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SK (Utility model), SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).  Published With international search report.	

(54) Title: INCONTINENCE PAD HAVING IMPROVED SECUREMENT SYSTEM

## (57) Abstract

An incontinence pad which is to be secured to a pant. The incontinence pad has a pair of end edges and a pair of side edges, a liquid pervious topsheet, a liquid impervious backsheet secured to the topsheet, and an absorbent core intermediate the topsheet and the backsheet. A pair of spaced apart securement patches are positioned adjacent each end edge of the incontinence pad. A unitary release strip bridges the securement patches.



**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon	KR	Republic of Korea	PL	Poland		
CN	China	KZ	Kazakhstan	PT	Portugal		
CU	Cuba	LC	Saint Lucia	RO	Romania		
CZ	Czech Republic	LI	Liechtenstein	RU	Russian Federation		
DE	Germany	LK	Sri Lanka	SD	Sudan		
DK	Denmark	LR	Liberia	SE	Sweden		
EE	Estonia			SG	Singapore		

**INCONTINENCE PAD  
HAVING IMPROVED SECUREMENT SYSTEM**

FIELD OF THE INVENTION

The present invention relates to articles which absorb and/or contain bodily exudates. More particularly, the invention relates to disposable incontinence pads having an improved securement system.

BACKGROUND OF THE INVENTION

Disposable incontinence pads used in combination with reusable pants are well known in the art. Also, the securement of such incontinence pads to the pants is also known in the art.

In particular, incontinence pads having a pair of adhesive patches positioned adjacent each end edge of the pad have been found to be effective in securing the incontinence pad to the pant. Typically, each adhesive patch is covered with an individual release member or patch. The release patch serves to protect the adhesive from being contaminated prior to use and from sticking to a surface other than the pant prior to use. However, grasping and removing four small pieces of release paper can be difficult and tedious.

Accordingly, it would be desirable to provide an incontinence pad with a release strip which is easy to grasp and remove.

SUMMARY OF THE INVENTION

The present invention is directed to an incontinence pad which is to be secured to a pant. The incontinence pad has a pair of end edges and a pair of side edges. The incontinence pad comprises a liquid pervious topsheet; a liquid impervious backsheet secured to the topsheet; and an absorbent core intermediate the topsheet and the backsheet. At least a pair of securement patches are positioned adjacent one of the end edges of the incontinence pad. The patches are spaced apart from one another. A unitary release strip bridges the securement patches. Most preferably, a pair of securement patches are positioned adjacent each end edge of the incontinence pad and a unitary release strip bridges each pair of securement patches.

10 The securement patches may have a shape selected from the group consisting of rectangular, round, square, triangular, oval, oblong, diamond, pentagonal, and chevron.

The securement patches preferably comprise an adhesive patch. However, the securement patches may comprise a hook fastening material, or a combination  
15 adhesive patch and hook fastening material.

### BRIEF DESCRIPTION OF THE DRAWINGS

20 While the specification concludes with claims particularly pointing out and distinctly claiming the subject matter which is regarded as the present invention, it is believed that the description will be better understood from the following descriptions which are taken in conjunction with the accompanying drawings in which like designations are used to designate substantially identical elements.

25

Figure 1 is a plan view of an incontinence pad of the present invention having portions cut away to reveal the underlying structure with the garment-facing surface of the pad facing the viewer.

Figure 2 is a plan view of an alternative embodiment of an incontinence pad of the present invention with the garment-facing surface of the pad facing the viewer.

5        Figure 3 is a plan view of an alternative embodiment of an incontinence pad of the present invention with the garment-facing surface of the pad facing the viewer.

### DETAILED DESCRIPTION OF THE INVENTION

10

As used herein, the term "absorbent article" refers to devices which absorb and contain body exudates, and more specifically, refers to devices which are placed against or in proximity to the body of the wearer to absorb and contain the various exudates discharged from the body. The term "disposable" is used herein to describe  
15 absorbent articles which generally are not intended to be laundered or otherwise restored or reused as an absorbent article (i.e., they are intended to be discarded after a single use and, preferably, to be recycled, composted or otherwise disposed of in an environmentally compatible manner). As used herein, the term "joined" encompasses configurations whereby an element is directly secured to another  
20 element by affixing the element directly to the other element, and configurations whereby an element is indirectly secured to another element by affixing the element to intermediate member(s) which in turn are affixed to the other element.

A preferred embodiment of an absorbent article of the present invention is  
25 the disposable incontinence pad (20), shown in Figure 1. As used herein, the term "incontinence pad" refers to an absorbent article worn by incontinent persons in combination with an elasticized pant. The incontinence pad (20) has a length dimension of at least about 300 mm and a width dimension of at least about 100 mm. In order to function properly as an incontinence device, the incontinence pad  
30 must be able to absorb at least about 300 grams of fluid, such as urine. The absorbent capacity is determined according to the standard ISO 11 948-1 method.

Figure 1 is a plan view of the incontinence pad (20) of the present invention in a flat-out, state with portions of the structure being cut-away to more clearly show the construction of the incontinence pad (20). The portion of the incontinence pad (20) which faces the wearer is oriented towards the viewer. As shown in Figure 1, the incontinence pad (20) preferably comprises a liquid pervious topsheet (24); a liquid impervious backsheet (26); an absorbent core (28), which is positioned between the topsheet (24) and the backsheet (26). The periphery of the incontinence pad (20) is defined by the outer edges of the pad (20) in which the side or longitudinal edges (50) run generally parallel to the longitudinal centerline (100) of the pad (20) and the end edges (52) run between the longitudinal edges (50) generally parallel to the lateral centerline (110) of the pad (20).

The backsheet (26) is generally that portion of the pad (20) positioned adjacent the garment facing surface (45) of the absorbent core (28) which prevents the exudates absorbed and contained therein from soiling other articles which contact the pad (20), such as the pant to which the pad is secured or other clothing. In preferred embodiments, the backsheet (26) is impervious to liquids (e.g., urine) and comprises a thin plastic film such as a thermoplastic film having a thickness of about 0.012 mm (0.5 mil) to about 0.051 mm (2.0 mils). Suitable backsheet films include those manufactured by British Petroleum, Wasserburg Germany, sold under the trade name BPC "44118 LLD" COL 0022.

Other suitable backsheet materials may include breathable materials which permit vapors to escape from the pad (20) while still preventing exudates from passing through the backsheet (26). Exemplary breathable materials may include materials such as woven webs, nonwoven webs, composite materials such as film-coated nonwoven webs, and microporous films such as manufactured by Mitsui Toatsu Co., of Japan under the designation ESPOIR NO and by EXXON Chemical Co., of Bay City, TX, under the designation EXXAIRE. Suitable breathable composite materials comprising polymer blends are available from Clopay

Corporation, Cincinnati, OH under the name HYTREL blend P18-3097. Such breathable composite materials are described in greater detail in PCT Application No. WO 95/16746, published on June 22, 1995 in the name of E. I. DuPont and copending U.S. Patent Application Serial No. 08/744,487, filed on November 6, 1996 in the name of Curro. Other breathable backsheets including nonwoven webs and apertured formed films are described in U.S. Pat. No. 5,571,096 issued to Dobrin et al. on November 5, 1996. Each of these references is hereby incorporated by reference herein.

10       The backsheet (26) may be joined to the topsheet (24), the absorbent core (28) or any other element of the pad (20) by any attachment means known in the art. For example, the attachment means may include a uniform continuous layer of adhesive, a patterned layer of adhesive, an array of separate lines, spirals, or spots of adhesive, or combinations thereof. One preferred attachment means comprises an  
15       open pattern network of filaments of adhesive as disclosed in U.S. Patent 4,573,986 entitled "Disposable Waste-Containment Garment", which issued to Minetola et al. on March 4, 1986. Other suitable attachment means include several lines of adhesive filaments which are swirled into a spiral pattern, as is illustrated by the apparatus and methods shown in U.S. Patent 3,911,173 issued to Sprague, Jr. on  
20       October 7, 1975; U.S. Patent 4,785,996 issued to Ziecker, et al. on November 22, 1978; and U.S. Patent 4,842,666 issued to Werenicz on June 27, 1989. Each of these patents are incorporated herein by reference. Adhesives which have been found to be satisfactory are manufactured by H. B. Fuller Company of St. Paul, Minnesota and marketed as HL-1258. Alternatively, the attachment means may  
25       comprise heat bonds, pressure bonds, ultrasonic bonds, dynamic mechanical bonds, or any other suitable attachment means or combinations of these attachment means as are known in the art.

      The topsheet (24) is preferably positioned adjacent the body surface (47) of  
30       the absorbent core (28) and may be joined thereto and/or to the backsheet (26) by any attachment means known in the art. Suitable attachment means are described

above with respect to means for joining the backsheet (26) to other elements of the pad (20). In one preferred embodiment of the present invention, the topsheet (24) and the backsheet (26) are joined directly to each other in some locations and are indirectly joined together in other locations by directly joining them to other  
5 elements of the pad (20).

The topsheet (24) is preferably compliant, soft feeling, and non-irritating to the wearer's skin. Further, at least a portion of the topsheet (24) is liquid pervious, permitting liquids to readily penetrate through its thickness. A suitable topsheet (24)  
10 may be manufactured from a wide range of materials, such as porous foams; reticulated foams; apertured plastic films; or woven or nonwoven webs of natural fibers (e.g., wood or cotton fibers), synthetic fibers (e.g., polyester or polypropylene fibers), or a combination of natural and synthetic fibers. If the absorbent assemblies include fibers, the fibers may be spunbond, carded, wet-laid, meltblown,  
15 hydroentangled, or otherwise processed as is known in the art. One suitable topsheet (24) comprising a web of staple length polypropylene fibers is manufactured by Fiberweb Norrkoping Sweden, sold under trade name "E" (96), "C" (96), "F" (96).

Suitable formed film topsheets are described in U.S. Pat. No. 3,929,135,  
20 entitled "Absorptive Structures Having Tapered Capillaries", which issued to Thompson on December 30, 1975; U.S. Pat. No. 4,324,246 entitled "Disposable Absorbent Article Having A Stain Resistant Topsheet", which issued to Mullane, et al. on April 13, 1982; U.S. Patent 4,342,314 entitled "Resilient Plastic Web Exhibiting Fiber-Like Properties", which issued to Radel, et al. on August 3, 1982;  
25 U.S. Pat. No. 4,463,045 entitled "Macroscopically Expanded Three-Dimensional Plastic Web Exhibiting Non-Glossy Visible Surface and Cloth-Like Tactile Impression", which issued to Ahr, et al. on July 31, 1984; and U.S. Pat. No. 5,006,394 "Multilayer Polymeric Film" issued to Baird on April 9, 1991. Other suitable topsheets 30 are made in accordance with U.S. Pat. Nos. 4,609,518 and  
30 4,629,643 which issued to Curro et al. on September 2, 1986 and December 16, 1986, respectively, and both of which are incorporated herein by reference. Such



formed films are available from The Procter & Gamble Company of Cincinnati, Ohio as "DRI-WEAVE" and from Tredegar Corporation of Terre Haute, Indiana as "CLIFF-T."

5            Preferably, the topsheet (24) is made of a hydrophobic material or is treated to be hydrophobic in order to isolate the wearer's skin from liquids contained in the absorbent core (28). If the topsheet (24) is made of a hydrophobic material, preferably at least the upper surface of the topsheet (24) is treated to be hydrophilic so that liquids will transfer through the topsheet more rapidly. This diminishes the  
10            likelihood that body exudates will flow off the topsheet (24) rather than being drawn through the topsheet (24) and being absorbed by the absorbent core (28). The topsheet (24) can be rendered hydrophilic by treating it with a surfactant or by incorporating a surfactant into the topsheet. Suitable methods for treating the topsheet (24) with a surfactant include spraying the topsheet (24) material with the  
15            surfactant and immersing the material into the surfactant. A more detailed discussion of such a treatment and hydrophilicity is contained in U.S. Pat. No. 4,988,344 entitled "Absorbent Articles with Multiple Layer Absorbent Layers" issued to Reising, et al. on Jan. 29, 1991 and U.S. Pat. No. 4,988,345 entitled "Absorbent Articles with Rapid Acquiring Absorbent Cores" issued to Reising on  
20            Jan. 29, 1991. A more detailed discussion of some suitable methods for incorporating surfactant in the topsheet can be found in U.S. Statutory Invention Registration No. H1670, published on July 1, 1997 in the names of Aziz et al. Each of these references is hereby incorporated by reference herein.

25            Any portion of the topsheet (24) may be coated with a lotion as is known in the art. Examples of suitable lotions include those described in U.S. Pat. No. 5,607,760 entitled "Disposable Absorbent Article Having A Lotioned Topsheet Containing an Emollient and a Polyol Polyester Immobilizing Agent" which issued to Roe on March 4, 1997; U.S. Pat. No. 5,609,587 entitled "Diaper Having A  
30            Lotioned Topsheet Comprising A Liquid Polyol Polyester Emollient And An Immobilizing Agent" which issued to Roe on March 11, 1997; U.S. Pat. No.

5,635,191 entitled "Diaper Having A Lotioned Topsheet Containing A Polysilozane Emollient" which issued to Roe et al. on June 3, 1997; and U.S. Pat. No. 5,643,588 entitled "Diaper Having A Lotioned Topsheet" which issued to Roe et al. on July 1, 1997. The topsheet may also include or be treated with antibacterial agents, some  
5 examples of which are disclosed in PCT Publication No. WO 95/24173 entitled "Absorbent Articles Containing Antibacterial Agents in the Topsheet For Odor Control" which was published on September 14, 1995 in the name of Johnson. Further, the topsheet (24), the backsheet (26) or any portion of the topsheet or backsheet may be embossed and/or matte finished to provide a more cloth like  
10 appearance.

The absorbent core (28) may comprise any absorbent material which is generally compressible, conformable, non-irritating to the wearer's skin, and capable of absorbing and retaining liquids such as urine and other certain body exudates.  
15 The absorbent core (28) may be manufactured in a wide variety of sizes and shapes (e.g., rectangular, hourglass, "T"-shaped, asymmetric, etc.) and may comprise a wide variety of liquid-absorbent materials commonly used in disposable diapers and other absorbent articles such as comminuted wood pulp, which is generally referred to as airfelt. Examples of other suitable absorbent materials include creped cellulose  
20 wadding; meltblown polymers, including coform; chemically stiffened, modified or cross-linked cellulosic fibers; tissue, including tissue wraps and tissue laminates; absorbent foams; absorbent sponges; superabsorbent polymers; absorbent gelling materials; or any other known absorbent material or combinations of materials.

25 The configuration and construction of the absorbent core (28) may also be varied (e.g., the absorbent core(s) or other absorbent structure(s) may have varying caliper zones, a hydrophilic gradient, a superabsorbent gradient, or lower average density and lower average basis weight acquisition zones; or may comprise one or more layers or structures). However, the total absorbent capacity of the absorbent  
30 core (28) should be compatible with the design loading and the intended use of the pad (20).

Exemplary absorbent structures for use as the absorbent assemblies are described in U.S. Patent 4,610,678 entitled "High-Density Absorbent Structures" issued to Weisman et al. on September 9, 1986; U.S. Patent 4,673,402 entitled "Absorbent Articles With Dual-Layered Cores" issued to Weisman et al. on June 16, 1987; U.S. Patent 4,834,735, entitled "High Density Absorbent Members Having Lower Density and Lower Basis Weight Acquisition Zones", issued to Alemany et al. on May 30, 1989; U.S. Patent 4,888,231 entitled "Absorbent Core Having A Dusting Layer" issued to Angstadt on December 19, 1989; U.S. Pat. No. 5,137,537 entitled "Absorbent Structure Containing Individualized, Polycarboxylic Acid Crosslinked Wood Pulp Cellulose Fibers" which issued to Herron et al. on August 11, 1992; and U.S. Patent 5,147,345 entitled "High Efficiency Absorbent Articles For Incontinence Management" issued to Young et al. on September 15, 1992; U.S. Pat. No. 5,342,338 entitled "Disposable Absorbent Article For Low-Viscosity Fecal Material" issued to Roe on August 30, 1994. Each of these patents is incorporated herein by reference.

The pad 20 also includes a securement system (40) for securing the pad (20) in a pant. The securement system (40) preferably comprises at least a pair of patches (44) positioned on the backsheet (26) adjacent one end edge (52) of the pad (20). Even more preferably, the securement system (40) comprises a pair of patches (44) positioned on the backsheet (26) adjacent each end edge (52) of the pad (20). As can be seen in Figure 1 the patches (44) are spaced apart from one another. It has been found that spacing the patches (44) from one another provides the needed securement of the pad (20) to a pant while maintaining the desired freedom of movement for the pad/pant system to ensure wearer comfort. For example, it has been found that securing the entire end edge (52) of the pad (20) to a pant provides very good securement, but unnecessarily restricts the movement of the pant and also adds unnecessarily to the cost of the product.

The patches (44) preferably comprise a pressure sensitive adhesive. A suitable pressure sensitive adhesive is sold by 3M Health Care, St. Paul, MN 55144-1000.

5       The patches (44) may be rectangular in shape having a size of about 50 millimeters x 30 millimeters. However, the patches (44) may have other shapes such as but not limited to round, square, triangular, star, oval, oblong, diamond, pentagonal, and chevron. The patches (44) may also be colored for ease of identification.

10

To prevent contamination of the adhesive patches (44) and to prevent the patches from sticking to the pant prematurely the adhesive patches (44) are covered with a unitary release strip (46). The release strip (46) may be made of poly film (e.g., silicone coated polyethylene film), kraft paper, calendered paper, or any other  
15       materials well known in the art for such purposes.

Preferably the face of the release strip (46) which contacts the adhesive patches (44) has a release coating, such as silicone, to facilitate the removal of the release strip (46) from the patches (44). Suitable release coatings are marketed by  
20       Akrosil of Menasha, Wisconsin as Silox 4R/O and as Silox C1S. If desired, the outwardly oriented face of the release strip (46) may further comprise indicia, such as advertising or usage instructions thereon. In addition or alternatively, the release strip 46 may be colored for easy identification. In addition, the release strip 46 in the front of the pad (20) may have one color while the release strip (46) in the back  
25       of the pad (20) may have another color.

The unitary release strip (46) bridges a pair of patches (44). A component, such as a release strip (46) is considered unitary if it cannot be divided or disassembled without tearing or unintended gross separation. It is not necessary that  
30       a unitary component be made of a single material but, rather that such component cannot be disassembled from and subsequently reassembled into the original

configuration. Components are considered to be "bridged" if they are connectively spanned by an independent component.

It is important that the unitary release strip (46) be conveniently and easily manipulated by the wearer. With a pad (20) having the unitary release strip (46) according to this invention, the pad (20) can be positioned on the wearer, the pant can then be pulled over the pad, and then the caregiver or wearer can reach inside the pant grab the central portion (47) of the release strip (46) which is unattached to any portion of the pad (20), and peel off the unitary release strip (46) removing the end portions (48) of the release strip (46) from the patches (44) thereby uncovering both patches (44) with a single motion. The end portions (48) are generally those portions of the release strip (46) which are secured to the patches (44) prior to removal of the release strip (46).

In an another embodiment shown in Figure 2, the securement system (40) comprises three patches (44) positioned on the backsheet (26) adjacent each end edge (52) of the pad (20). As can be seen in Figure 2 the patches (44) are spaced apart from one another. The unitary release strip (46) bridges all three patches (44). The addition of the third patch (44) between the two outer patches helps to maintain the release strip (46) in place while the pant is pulled on over the pad (20) during application to the wearer.

In the embodiment shown in Figure 1, the patches (44) have a width dimension equal to that of the release strip (46). In the embodiment shown in Figure 2, the patches (44) have a width dimension less than that of the release strip (46).

In another embodiment shown in Figure 3, the securement system (40) comprises a pair of patches (44) positioned on the backsheet (26) adjacent each end edge (52) of the pad (20). The unitary release strip (46) comprises a means (120) for initiating removal of the release strip (46) at or near its center, preferably at the longitudinal centerline (100). This may be accomplished, for example, by any

appendage to the release strip (46) which enables it to be grasped near the longitudinal centerline (100) of the pad (20). For example, the release strip (46) may be shaped to have a tab (122) which the user may grasp.

5           The patches (44) may comprise a hook fastening material or combination hook fastening material and adhesive although any other known fastening means is generally acceptable. Suitable hook fastening materials are disclosed in U.S. Patent 4,846,815 issued to Scripps on July 11, 1989; U.S. Patent 4,894,060 issued to Nestegard on January 16, 1990; U.S. Pat. No. 5,151,092 issued to Buell on  
10       September 9, 1992; and U.S. Pat. No. 5, 221,274 issued to Buell on June 22, 1993. The fastening system may also provide a means for holding the article in a disposal configuration as disclosed in U.S. Pat. No. 4,963,140 issued to Robertson et al. on October 16, 1990. Each of these patents is incorporated herein by reference.


15           While particular embodiments of the present invention have been illustrated and described, it would be obvious to those skilled in the art that various other changes and modifications can be made without departing from the spirit and scope of the invention. It is therefore intended to cover in the appended claims all such changes and modifications that are within the scope of this invention.

## WHAT IS CLAIMED IS:


1. An incontinence pad (20) to be secured to a pant, said incontinence pad (20) having a pair of end edges (52) and a pair of side edges (50), said incontinence  
5 pad comprising  
a liquid pervious topsheet (24);  
a liquid impervious backsheet (26) secured to said topsheet;  
an absorbent core (28) intermediate said topsheet and said backsheet;  
at least a pair of securement patches (44) positioned adjacent one of said end  
10 edges of said incontinence pad, said securement patches being spaced from one  
another; and  
characterized in that  
a unitary release strip (46) bridges said securement patches.
- 15 2. The incontinence pad of claim 1 comprising a pair of securement patches  
positioned adjacent each end edge of said incontinence pad and a unitary release  
strip bridging each pair of securement patches.
- 3 The incontinence pad of claim 1 or claim 2 wherein said securement patches  
20 have a shape selected from the group consisting of rectangular, round, square,  
triangular, star, oval, oblong, diamond, pentagonal, and chevron.
4. The incontinence pad of any one of the preceding claims wherein said  
securement patches comprise an adhesive patch.
- 25 5. The incontinence pad of any one of claims 1, 2 or 3 wherein said securement  
patches comprise a hook patch.
6. The incontinence pad of any one of claims 1, 2 or 3 wherein said securement  
30 patches comprise a combination adhesive and hook patch.

7. The incontinence pad of any one of claims 1, 2 or 3 wherein said securement patches have a width dimension equal to a width dimension of said release strip.
8. The incontinence pad of any one of claims 1, 2 or 3 wherein said securement patches have a width dimension less than a width dimension of said release strip.
9. An incontinence pad (20) to be secured to a pant, said incontinence pad having a pair of end edges (52) and a pair of side edges (50), said incontinence pad comprising  
a liquid pervious topsheet (24);  
a liquid impervious backsheet (26) secured to said topsheet;  
an absorbent core (28) intermediate said topsheet and said backsheet;  
a pair of securement patches (44) positioned adjacent each end edge of said incontinence pad, said securement patches being spaced from one another; and  
characterized in that  
a unitary release strip (46) bridges said securement patches.
10. The incontinence pad of claim 9 wherein said securement patches have a shape selected from the group consisting of rectangular, round, square, triangular, oval, oblong, diamond, pentagonal, and chevron.
11. The incontinence pad of either claim 9 or claim 10 wherein said securement patches comprise an adhesive patch.
12. The incontinence pad of any one of claims 9, 10 or 11 wherein said securement patches comprise a hook patch.
13. The incontinence pad of any one of claims 9, 10 or 11 wherein said securement patches comprise a combination adhesive and hook patch.




**Fig. 1**

2/3

**Fig. 2**

3/3

**Fig. 3**



# INTERNATIONAL SEARCH REPORT

I. International Application No  
PCT/IB 99/00052

A. CLASSIFICATION OF SUBJECT MATTER  
IPC 6 A61F13/15 A61F13/56

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)  
IPC 6 A61F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 0 302 523 A (KIMBERLY CLARK CO) 8 February 1989 see page 4, line 20 - line 22 see page 5, line 21 - line 28; figures ---	1-4,8
X	WO 97 41818 A (PROCTER & GAMBLE) 13 November 1997 see page 27, paragraph 2 - paragraph 3; figure 12	1,3,4, 8-11
Y	---	2,5,7,12
Y	FR 2 093 481 A (KIMBERLY CLARK CO) 28 January 1972 see page 5, line 39 - page 6, line 4; figure 5 --- -/--	2,7

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

\* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

16 April 1999

Date of mailing of the international search report

26/04/1999

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

Douskas, K

# INTERNATIONAL SEARCH REPORT

International Application No

PCT/IB 99/00052

## C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	WO 85 03430 A (BRIER MICHAEL I) 15 August 1985 see page 7, paragraph 2 - paragraph 4 ----	5,12
A	US 4 690 680 A (HIGGINS MAUREEN L) 1 September 1987 see claims; figures ----	1,9
A	EP 0 607 986 A (MCNEIL PPC INC) 27 July 1994 see figures -----	1,9

# INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/IB 99/00052

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
EP 0302523	A	08-02-1989	US 4804380 A	14-02-1989
			AT 104536 T	15-05-1994
			AU 625733 B	16-07-1992
			AU 2027488 A	09-02-1989
			CA 1306833 A	01-09-1992
			DE 3889161 D	26-05-1994
			DE 3889161 T	04-08-1994
			ES 2051281 T	16-06-1994
			HK 21495 A	24-02-1995
			JP 1070051 A	15-03-1989
			KR 132213 B	14-04-1998
			PH 24928 A	26-12-1990
			PT 88211 A,B	30-06-1989
			SG 149594 G	12-05-1995
WO 9741818	A	13-11-1997	AU 2818597 A	26-11-1997
			CA 2253385 A	13-11-1997
FR 2093481	A	28-01-1972	DE 2123515 A	25-11-1971
			GB 1349962 A	10-04-1974
			US 3672371 A	27-06-1972
			ZA 7102969 A	26-01-1972
			CA 960952 A	14-01-1975
			US 3674595 A	04-07-1972
WO 8503430	A	15-08-1985	US 4664663 A	12-05-1987
			AU 3990285 A	27-08-1985
			EP 0170700 A	12-02-1987
US 4690680	A	01-09-1987	CA 1286856 A	30-07-1991
			JP 63054161 A	08-03-1988
EP 0607986	A	27-07-1994	AU 683028 B	30-10-1997
			AU 5390994 A	28-07-1994
			BR 9400310 A	09-08-1994
			CA 2113757 A	22-07-1994
			GR 1002060 B	28-11-1995
			JP 6339498 A	13-12-1994
			NZ 250700 A	28-05-1996